


## 3H Series 3/2 Way Hand Control Valve



### Symbol



### Product Code System

3H	2	10	—	08
型号/Model	系列代号/Series Code	位置/Position		接管螺纹 Port Thread
3H: 二位三通手扳阀 3H: 3/2 Way Hand Control Valve	2: 200系列/Series 3: 300系列/Series	10: 双位置/Two-Position		06: G1/8 08: G1/4 10: G3/8

### Example

For the order of two-position 3H2 series hand control valve which port thread is 1/8", the correct order code is : 3H210-06

### Specification

型号 / Model	3H210-06	3H210-08	3H310-08	3H310-10
工作介质/ Fluids	经过滤的压缩空气 / The constrigent after filtered			
位置数/ Position	二位三通/ 3/2 Way			
有效截面积/ Efficient Sectional Area	14mm <sup>2</sup> (CV=0.78)	16mm <sup>2</sup> (CV=0.89)	25mm <sup>2</sup> (CV=1.4)	30mm <sup>2</sup> (CV=1.68)
接管螺纹/Port Thread	进气/Supply=出口/Export=排气/Exhaust=G1/8	进气/Supply=出口/Export=G1/4 排气/Exhaust=G1/8	进气/Supply=出口/Export=排气/Exhaust=G1/4	进气/Supply=出口/Export=G3/8 排气/Exhaust=G1/4
润滑/ Lubrication	不需要/Not Required			
使用压力 / Operating Pressure	0~0.8MPa			
最大耐压力 / Max Pressure	1.2 MPa			
工作温度 / Operating Temperature	-5-60			

### Dimensions

